

# ENQUIRY FORM

## ROTARY VALVES

Scheuch COMPONENTS GmbH offers a wide range of rotary valves. Please complete this form in full so we can prepare a quotation in line with your needs. We look forward to working with you to create a tailor-made solution for your application.

### YOUR DETAILS

Company: \_\_\_\_\_  
Address: \_\_\_\_\_  
Contact person: \_\_\_\_\_  
Project: \_\_\_\_\_

Telephone number: \_\_\_\_\_  
E-mail address: \_\_\_\_\_  
Date: \_\_\_\_\_  
Number of pieces: \_\_\_\_\_

### YOUR REQUIREMENTS

**Design** (if already known)       zsg     zsl     zss     zss-ck     zsm

**Execution information**

#### Design data

Conveyed medium \_\_\_\_\_  
Lowest medium density \_\_\_\_\_ kg/m<sup>3</sup>  
Characteristics of the conveyed medium \_\_\_\_\_  
(abrasive, humidity, dust characteristics ...)  
Temperature of the conveyed medium \_\_\_\_\_ °C  
Discharge rate or volume \_\_\_\_\_ t/h \_\_\_\_\_ m<sup>3</sup>/h  
Differential pressure \_\_\_\_\_ Pa  
Casing hole, wear-resistant       yes       no  
(Hard chrome-plated: possible for zsg, zss & zsm)

Ambient temperature      from \_\_\_\_\_ to \_\_\_\_\_ °C  
Top coat colour \_\_\_\_\_ RAL  
Explosion protection:  
 inside no zone/outside no zone  
 inside zone 20 (21)/outside no zone  
 inside zone 20 (21)/outside zone 22  
 inside protective system/outside no zone  
 inside protective system/outside zone 22

#### Drive

3-phase geared motor \_\_\_\_\_  
Frequency \_\_\_\_\_ Hz  
Voltage \_\_\_\_\_ V  
Temperature sensor       yes       no  
Standstill heating       yes       no

#### Options

Weather protection       yes       no  
Speed monitoring       yes       no  
Terminal box       yes       no  
Trace heating       yes       no  
Insulation       yes       no

**Further information** (dust characteristics, KST (dust deflagration) index, minimum ignition energy, etc.)

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

**Submit enquiry**