DISTRIBUTION CONTAINER WITH AGITATOR


PRODUCT DATA SHEET




Space-saving design and flexible container sized for efficient storage organisation

TECHNICAL DATA

Available nominal widths	800, 1,200 and 2,000 mm
Container height	1,000 mm
Volume	0.5 m³, 1 m³ and 3 m³
Agitator gear	At NW 800 and NW 1,200
Drive output	1.1 kW
Output speed	5.6 U/min
Agitator gear	At NW 2,000
Drive output	4.0 kW
Output speed	7.0 U/min
Particle size/grain	Wood chips P16 – P45 (EN 14961)





DESIGN

- Integrated agitator
- Maintenance opening with inspection window and safety limit switch
- Height-adjustable tubular feet
- Container lid with cut-outs to customer specifications
- Up to 3 discharge openings

FURTHER OPTIONS

- For all NW: container extended by 1,000 mm
- At NW 1,200: special height of 626 mm
- Ceiling suspension
- Level monitoring

Data sheet number: 202607
Subject to technical changes.

Scheuch COMPONENTS GmbH
Weierfing 68, 4971 Aurolzmünster
Austria

Phone +43 7752 905 - 0
E-Mail office@scheuch-components.com
Web www.scheuch-components.com

For more information on the distribution container, see our website.